

**Product:** BoothSaver™ 2092 Double Tacky Flashzone Film is coated on both sides with a crater-tested, residue-free, pressure-sensitive adhesive. The high tack backside of this film adheres itself securely to protect walls and doors from paint overspray. Removing the outside release film exposes a high tack surface that captures and holds airborne contaminants. This film also can be used on some low surface energy materials (such as Formica) commonly used in air showers. The metallic color of this film helps keep the area look cleaner and brighter.



**Benefits:** Protects flashzone walls and other steel surfaces from contamination.  
High tack adhesive on surface attracts and holds dirt seeds.  
Antistatic (GB/T 1410-2006  $\leq 4.0 \times 10^{11} \Omega/\square$ )  
Resistant to most paint shop chemicals.  
Save setup time by applying 4-5 layers before peeling  
Solid non-hazardous waste disposal.

**Usage:** BoothSaver™ 2092 is available in 0.92m x 50m rolls. The film's backside has a high strength unprotected adhesive coating which is applied directly to the wall. To use film:

- Prepare surface to be protected by cleaning with alcohol or a residue free cleaner.
- Apply film to wall directly from the roll and cut to size with scissors or knife.
- Once in place, find edge of clear protective release film layer and remove by pulling down, to expose high tack surface.
- To remove film, lift its edge from the protective surface and peel away. Fold the outer surface onto itself in order to further seal contaminated layer.
- Dispose of properly as solid, non-hazardous waste.

**Part #:** M17015-36-50 (Gray 36" x 55yd; 0.91m x 50m)